

S-CMH1

Wireless CamCatch



- 2.5 inch LCD to display sweep images
- 45.2 * 27mm LCM frequency display and function setting
- Frequency sweep Range 0.9~3GHz / 5~6GHz
- Manual / Auto / Fixed sweep operation mode simple operation
- Buzzer and vibration alert
- Integrated 20MHz ~ 6GHz RF Detector function
- Can be set 8 fixed of frequencies scan
- 6 Sections threshold adjustment
- 3000mA standard accessories replaceable lithium battery
- Can display the sweep image is NTSC or PAL
- Two kinds of frequency spectrum display mode selection

Display 1	45.2*27mm LCD
Display 2	2.5" LCD
Antenna Connector	SMA Connector
Sweep Range	0.9~3GHz / 5~6GHz
Auto-Sweep cycle time	10~20 sec / cycle (L~H)
Threshold Adjustment	6 Sections Threshold High -50dBm Medium High -55dBm Medium -60dBm Medium Low -65dBm Low -70dBm Ultra Low -80dBm
RF Detector Frequency Range	20MHz~6GHz
Video Input	2.5" Phone Jack NTSC / PAL Auto Detection
Video / Audio Output	2.5" Phone Jack
Alarm output	2.5" Phone Jack
Power Input	DC 5V / 2A
Battery Type	DC 3.7V 3000mA Lithium battery
Operation Mode	Auto / Manual / Fixed
Battery life time	4.4 Hours
Operating Temperature	-10~50°
Operating Humidity	10~95%
Weight	140g
Dimension	99.5*69.5*24.7 mm (Without Battery)

Absovision reserves the right, without liability or prior notice, to revise or discontinue certain items

