

# RX-12001 & RX-24001 & RX-33001

## AV Wireless Receiver Series

- Video/Audio Wireless Receiver
- 8 channels DIP switch selectable
- A/B Channel Group Switchable
- Auto/Manually DIP switcher
- Ultra compact size
- Wide DC voltage in supported



Model Name	RX-12001	RX-24001	RX-33001
Frequency Band	1200MHz	2400MHz	3300MHz
Available Channel	8 Ch	8 Ch	8 Ch
Audio Subcarrier	5.5MHz	6.5MHz	6.5MHz
Operating Voltage	DC5V~16V		
Power Consumption	< 2.2W		
Operating Humidity	20~90%		
Operating Temperature	0~60°		
Video output	5 ohm load		
Audio output	1K load		
Channel Selection	Dip Switch		
Antenna Connector	SMA Connector		
Frequency Lock Method	Digital Phase Lock Loop		
Weight	45g (Without Antenna/Wire)		
Dimension	69.5*47.5*16 mm (L*W*H)		

item	RX-12001		RX-24001		RX-33001	
	(A)	(B)	(A)	(B)	(A)	(B)
CH 1	1080	1080	2410	2410	3330	3250
CH 2	1120	1120	2430	2430	3350	3270
CH 3	1160	1160	2450	2450	3370	3290
CH 4	1200	1100	2470	2470	3390	3310
CH 5	1010	1040	2370	2370	3410	3490
CH 6	1040	1180	2390	2390	3430	3510
CH 7	1240	1180	2490	2490	3450	3530
CH 8	1280	1180	2510	2510	3470	3550

Absovision reserves the right, without liability or prior notice, to revise or discontinue certain items

